

CPP 22: 2D Materials III (joint session HL/CPP)

Time: Tuesday 9:30–12:15

Location: POT 81

CPP 22.1 Tue 9:30 POT 81

Sub-THz detection in two dimensional systems and CVD graphene heterostructures — FRANZISKA LINSS¹, VINCENT STRENZKE¹, PAI ZHAO¹, CHITHRA S. SHARMA¹, LARS TIEMANN¹, QIN HUA², and ROBERT H. BLICK¹ — ¹Center for Hybrid Nanostructures, Universität Hamburg, Luruper Chaussee 149, 22761 Hamburg, Germany — ²Suzhou Institute of Nanotech and Nanobionics (SINANO) of the Chinese Academy of Sciences (CAS), China

Electromagnetic radiation in the THz range can induce surface plasmons, i.e., a collective motion of electrons, in graphene-based devices. We fabricated a field-effect-transistor with asymmetric dual-grating gates (ADGG) to detect sub-THz radiation using large-scale graphene that was synthesized by chemical vapor deposition (CVD). The CVD graphene sheet is encapsulated between two flakes of hBN and placed on a highly doped Si wafer that acts as a back gate. The ADGG was structured on the top hBN flake. The control of the carrier concentration via electrostatic gates is crucial to match the resonance condition of the plasmons. The sample was characterized by sweeping the top gate voltage from -1 V to 2 V and the charge neutrality point was reached at a top gate voltage of 0.87 V at 4.2 Kelvin. Furthermore, we used a high electron mobility transistor (HEMT) to detect THz radiation, where the detection mechanism is based on a mixing with a reference radiation in a nonlinear medium. In this device, we can demonstrate sub-THz radiation at room temperature.

CPP 22.2 Tue 9:45 POT 81

Theory of non-local Andreev reflection through Andreev molecular states in graphene Josephson junctions — ANDOR KORMÁNYOS¹, EDUÁRD ZSURKA¹, NOEL PLASZKÓ¹, and PÉTER RAKYTA^{1,2} — ¹Department of Physics of Complex Systems, Eotvos Lorand University, Budapest, Hungary — ²Wigner Research Center for Physics, 29-33 Konkoly-Thege Miklos Str., H-1121 Budapest, Hungary

We propose that a device composed of two vertically stacked monolayer graphene Josephson junctions can be used for Cooper pair splitting. The hybridization of the Andreev bound states of the two Josephson junctions can facilitate non-local transport in this normal-superconductor hybrid structure, which we study by calculating the non-local differential conductance. Assuming that one of the graphene layers is electron and the other is hole doped, we find that the non-local Andreev reflection can dominate the differential conductance of the system. Our setup does not require the precise control of junction length, doping, or superconducting phase difference, which could be an important advantage for experimental realization.

CPP 22.3 Tue 10:00 POT 81

Quantum Hall measurements near electric field controlled Lifshitz transitions in trigonally warped bilayer graphene — MARTIN STATZ, ANNA SEILER, JONAS PÖHLS, MORITZ KNAAK, FRANCESCA FARLORSI, and THOMAS WEITZ — 1st Physical Institute, Faculty of Physics, University of Göttingen, Friedrich-Hund-Platz 1, Göttingen 37077, Germany

Various spontaneous symmetry broken phases such as Stoner ferromagnetism, spin-polarized superconductivity, a quantum anomalous Hall octet and a topologically non-trivial Wigner-Hall crystal phase have recently been reported in bilayer graphene (BLG) [1]. Since these interaction-driven phenomena are dictated by the ratio of the Coulomb and kinetic energy of carriers, they can be promoted by the formation of flat bands and a divergent density of states (DoS) near Lifshitz transitions (LT). Trigonally warped BLG at low vertical displacement fields (D-field) and carrier densities ($\sim 10^{11} \text{ cm}^{-2}$) displays one centre and three off-centre Dirac cones in each valley, and therefore offers a rich playground for correlated phases (CP) and changes in the Fermi surface topology by inducing charge density and D-field driven LT. Here, we report on quantum Hall measurements near charge density and D-field driven LT in trigonally warped BLG encapsulated in hexagonal boron-nitride in a dual-gated architecture with graphite contacts and graphite gates at 10 mK. We further outline our status on the temperature dependence of several CP in the aforementioned regimes.

[1] Seiler, A.M. et al. Nature 608, 298-302 (2022)

CPP 22.4 Tue 10:15 POT 81

Tuning electronic properties of graphene with a transferred ultrathin Ga₂O₃ encapsulation — MATTHEW GEBERT¹, SEMONTI BHATTACHARYYA², CHRISTOPHER BOUNDS¹, NITU SYED^{3,4}, TORBEN DAENEKE⁴, and MICHAEL S. FUHRER¹ — ¹School of Physics and Astronomy, Monash University, Melbourne — ²Leiden Institute of Physics, Leiden University, Leiden — ³School of Physics, The University of Melbourne, Parkville, Melbourne — ⁴School of Engineering, RMIT University, Melbourne

Although graphene holds immense potential for future electronics and spintronics, it is tricky to find a suitable large-area encapsulation layer for graphene that enhances its properties. In this talk, I will demonstrate a large-area passivation layer for graphene by mechanical transfer of ultrathin Ga₂O₃ synthesized on the surface of liquid Ga metal.¹

Electrical measurements of millimetre-scale passivated and bare CVD graphene on SiO₂ substrate indicate that the passivated graphene maintains its high field effect mobility, desirable for applications. Surprisingly, the temperature-dependent resistivity is reduced in our passivated graphene over a range of temperatures below 230 K, due to the interplay of screening of the remote optical phonon modes of the SiO₂ by the high dielectric constant of Ga₂O₃, and the relatively high characteristic phonon frequencies of Ga₂O₃. Raman spectroscopy and electrical measurements indicate that Ga₂O₃ passivation also protects graphene from further processing such as plasma-enhanced atomic layer deposition of Al₂O₃.

1. Gebert, Bhattacharyya et al, Nano Lett, <https://doi.org/10.1021/acs.nano>

CPP 22.5 Tue 10:30 POT 81

Hopping transport in ultraclean dual graphite gated bilayer graphene — DAVID ALEXANDER DAREK EMMERICH¹, EIKE THOMAS ICKING^{1,2}, PHILIPP SCHMIDT^{1,2}, FRANK VÖLMEYER^{1,3}, KENJI WATANABE⁴, TAKASHI TANIGUCHI⁵, BERND BESCHOTEN¹, and CHRISTOPH STAMPFER^{1,2} — ¹RWTH Aachen University, Germany — ²Forschungszentrum Jülich, Germany — ³AMO GmbH, Advanced Microelectronic Center Aachen (AMICA), Germany — ⁴Research Center for Functional Material, Japan — ⁵International Center for Materials Nanoarchitectonics, Japan

Bernal-stacked bilayer graphene (BLG) is a material that has a unique property: BLG is intrinsically a semimetal, but becomes a semiconductor under the application of an out-of-plane displacement field. This controlled opening of a gate-tunable band gap makes it a promising material for realizing highly-tunable transistors and photodetectors. The limiting factor of BLG-based devices is disorder. Only by using graphitic bottom gates a true band insulating state was achieved in BLG, which exhibits a clean gap opening with faint signs of residual disorder. Using finite bias spectroscopy, we show that BLG devices with graphitic top and bottom gate electrodes exhibit extremely low disorder. We perform transport measurements down to the sub-Kelvin regime and analyse the temperature-dependent transport behaviour. For small displacement fields, where gap and disorder are expected to be of the same order of magnitude, the low-temperature hopping transport data are investigated concerning the dominant hopping mechanism.

15 min. break

CPP 22.6 Tue 11:00 POT 81

high responsivity monolayer MoS₂ photodetectors on cyclic olefin copolymer-passivated SiO₂ gate dielectric — EMAD NAJAFIDEHAGHANI¹, SIRRI BATUHAN KALKAN², ZIYANG GAN¹, JAN DREWNIOK², MICHAEL F. LICHTENEGGER², UWE HÜBNER³, ALEXANDER S. URBAN², ANTONY GEORGE¹, BERT NICKEL², and ANDREY TURCHANIN¹ — ¹Friedrich Schiller University Jena, Institute of Physical Chemistry, Jena — ²Ludwig Maximilian University of Munich, Faculty of Physics, Munich — ³Leibniz Institute of Photonic Technology (IPHT), Jena

2D material-based photodetectors attracted significant research interest due to their high responsivity, flexibility and transparency. However, the trap states present at the surface of SiO₂ gate dielectrics diminishes the performance of 2D material-based photodetectors. To reduce the detrimental effect of SiO₂ surface traps, an ultrathin film (5 nm) of cyclic olefin copolymer (COC) layer is employed as a surface

passivator. Due to the reduction of the interface trap density, the photoresponsivity of the MoS₂ devices on passivated SiO₂ is enhanced by four orders of magnitude compared to non-passivated MoS₂ devices. Under optimized conditions a record photoresponsivity of 3×10^7 A/W in combination with a short response time is observed. Our findings show that the ultrathin COC passivation of the gate dielectric enables to probe exciting properties of the atomically thin 2D semiconductors.

CPP 22.7 Tue 11:15 POT 81

Atomic layer deposition of horizontal and vertical MoS₂/WS₂ heterostructures — ●CHRISTIAN TESSAREK, TIM GRIEB, ANDREAS ROSENAUER, and MARTIN EICKHOFF — Institut für Festkörperphysik, Universität Bremen

Beyond the properties of single two-dimensional (2D) layers, heterostructures made of 2D transition metal dichalcogenides promise new properties based on moiré physics and interlayer excitons.

Vertical and horizontal MoS₂ and WS₂ heterostructures were grown by atomic layer deposition (ALD) and analyzed by Raman and photoluminescence spectroscopy. The influence of the the ALD growth sequence, i.e. MoS₂/WS₂ vs. WS₂/MoS₂, was investigated. Elemental distribution of Mo and W in a horizontal heterostructure was studied by high resolution transmission electron microscopy and energy-dispersive X-ray spectroscopy. Additional high temperature annealing was performed to improve the structural and optical properties of the layers.

CPP 22.8 Tue 11:30 POT 81

Fully automated platform for 2D material flake detection using real-time machine learning techniques — ●JAN-LUCAS USLU, TAOUFIQ OUAI, BERND BESCHOTEN, LUTZ WALDECKER, and CHRISTOPH STAMPFER — JARA-FIT and 2nd Institute of Physics A, RWTH Aachen University, Aachen, Germany

As of today, most of fundamental experimental 2D material research is based on mechanically exfoliated flakes, finding suitable flakes for the fabrication of van der Waal heterostructures is time-consuming and time-critical part requiring expert knowledge and manpower.

In order to mitigate this problem, we demonstrate a simple and robust real time-capable algorithm based on Gaussian mixture models, a machine learning technique, to allow for a fast automated search of exfoliated flakes of different 2D materials in a single run with an automated microscope setup to analyze batches of exfoliated material.

The algorithm solves the task of automatically detecting various flakes on Si++/SiO₂ wafer dices, allows to index the location and segmentation of each flake and provides metrics such as size, thickness and shape.

The algorithm is evaluated on more than 500.000 images of different 2D materials including graphene and multilayer graphene, hexagonal boron nitride, transition metal dichalcogenides and 2D magnets.

CPP 22.9 Tue 11:45 POT 81

CVD Growth of Hexagonal Boron Nitride on CMOS-compatible Substrates — ●MAX FRANCK¹, JAREK DABROWSKI¹, MARKUS ANDREAS SCHUBERT¹, WALTER BATISTA PESSOA², DOMINIQUE VIGNAUD², LUC HENRARD³, CHRISTIAN WENGER^{1,4}, and MINDAUGAS LUKOSIUS¹ — ¹IHP - Leibniz-Institut für innovative Mikroelektronik, Im Technologiepark 25, 15236 Frankfurt (Oder), Germany — ²University Lille, CNRS, Centrale Lille, JUNIA ISEN, University Polytechnique Hauts de France, UMR 8520-IEMN F-59000 Lille, France — ³Department of Physics, Namur Institute of Structured Materials, University of Namur, Rue de Bruxelles 61, 5000 Namur, Belgium — ⁴Semiconductor Materials, BTU Cottbus-Senftenberg, Platz der Deutschen Einheit 1, 03046 Cottbus, Germany

Hexagonal boron nitride (hBN) is a two-dimensional insulator with a range of promising applications, including DUV optoelectronics and protection layers for high-mobility graphene. Most commonly, high-quality hBN is grown via CVD on catalytic transition metal substrates. However, the hBN films require transfer to CMOS-compatible substrates, which leaves residual metal contaminations at concentrations unacceptable for Si technology integration.[1] Therefore, growth of hBN thin films directly on CMOS-compatible substrates, such as Si, Ge or dielectrics, is desirable. We present recent results regarding CVD synthesis of well-oriented, few-layer hBN films on such substrates using borazine as a single-source precursor. Morphology and crystalline quality were characterized using XPS, AFM, Raman spectroscopy and TEM. [1] G. Lupina, J. Kitzmann, et al. ACS Nano 2015, 9, 4776-4785.

CPP 22.10 Tue 12:00 POT 81

Microwave plasma driven 2H-1T phase modulation of WSe₂ for improving NO₂ gas sensing performance — ●YU DUAN^{1,2}, SAM ZHANG², HUAPING ZHAO¹, and YONG LEI¹ — ¹Fachgebiet Angewandte Nanophysik, Institut für Physik & IMN MacroNano, Technische Universität Ilmenau, 98693 Ilmenau, Germany — ²Center for Advanced Thin Films and Devices, School of Materials and Energy, Southwest University, Chongqing, 400715, China

Transition metal dichalcogenides (TMDs) have been widely used in recent years for gas sensors. Herein, we constructed a simple microwave plasma device by modifying a home microwave oven for surface treatment of WSe₂. A 1T/2H hybrid phase structure was constructed by phase modulation and Se vacancies were introduced to effectively enhance its gas sensing performance. The sample after 60 s of treatment exhibited high response (52.24%), fast response rate (49.8 s), short recovery time (14.9 mins), and outstanding stability and selectivity for 1 ppm NO₂ at room temperature. In addition, molecular model of the microwave plasma-treated sample is proposed, leading to the intrinsic mechanism of its performance enhancement. It is demonstrated that microwave plasma treatment is a promising method to enhance the gas sensing performance of TMDs.